

Project Name:
Part Number:
Fixture Type
Notes:

## HK Tunable Recessed Linear Light

### FEATURES

#### CCT & CRI

CCT Selectable 3000K / 3500K / 4000K, CRI > 80

#### WATTAGE SELECTABLE

Selectable Watt packages ranging from 20W - 80W

#### AMBINET TEMPERATURE

Suitable for use in 32°F to 104°F (0°C to 40°C)

#### EFFICACY

Up to 104 lumens per watt

#### HOUSING

Body consists of extruded aluminum

#### MOUNTING

Recessed mounting

#### ELECTRICAL

Standard 120/277V with 50/60Hz, 1-10V dimming.

#### WARRANTY

5 year limited warranty. Comprehensive warranty terms can be located on [www.orelighting.com](http://www.orelighting.com)



HK 4 & 8 FT - 4 & 6 inch Linear Light



### ORDERING INFORMATION


EXAMPLE: HK 4FT 4" WS SCT WT UNV D

Series	Length	Width	Wattage Selectable	CCT Selectable	Finish	Voltage	Dimmable
HK	4FT 4 feet	4" 4 inch	20W	3000K	WT White	UNV 120 - 277V	D 1 - 10V dimming
		6" 6 inch	30W 40W	3500K 4000K			
HK	8FT 8 feet	4" 4 inch	40W				
		6" 6 inch	60W 80W				




## DIMENSIONS


### HK 4FT 4 Inch Linear Light




### HK 4FT 6 Inch Linear Light



### HK 8FT 4 Inch Linear Light



### HK 8FT 6 Inch Linear Light



# ORE LIGHTING

## PERFORMANCE DATA

PART NUMBER	WATTAGE	3000K		3500K		4000K	
		LUMENS	CRI	LUMENS	CRI	LUMENS	CRI
HK 4FT 4" & 6"	20W	2,080	80+	2,085	80+	2,087	80+
	30W	3,120	80+	3,122	80+	2,123	80+
	40W	4,160	80+	4,162	80+	4,163	80+
HK 8FT 4"	80W	8,320	80+	8,322	80+	8,323	80+
HK 8FT 6"	80W	8,320	80+	8,324	80+	8,325	80+

## PROJECTED LED LUMEN MAINTENANCE

Operating Hours	0	25,000	50,000	100,000
Lumen Maintenance Factor	1	0.97	0.97	0.96

## ELECTRICAL LOAD

WATTAGE	CURRENT (A)			
	120V	208V	240V	277V
20W	0.17	0.11	0.08	0.07
30W	0.25	0.16	0.13	0.11
40W	0.33	0.19	0.17	0.14
80W	0.67	0.38	0.36	0.29

