

Project Name:
Part Number:
Fixture Type
Notes:

VALA M3R 3.8" Recessed Tunable Architectural Linear Light

FEATURES

CCT & CRI

CCT Selectable 3000K / 3500K / 4000K, CRI > 80

AMBINET TEMPERATURE

Suitable for use in 32°F to 104°F (0°C to 40°C)

EFFICACY

115 LM/W, 1,200 Lumens/ft, 10 Watts/ft

HOUSING

Extruded aluminum housing with powder coat finish

MOUNTING

Recessed: Compatible with most 15/16" and 9/16" T-grid ceiling or dry ceiling

Surface: For direct ceiling and wall mounting



DRIVERS

Standard 120 - 277V, 0 - 10V Dimming down to 10%. Power factor >0.9, THD <20%

120V connections up to 40ft. 277V connections up to 100ft



ORDERING INFORMATION

EXAMPLE: VALA M3R 2FT SCT TD WT UNV LPS

Series	Width	Length	CCT Selectable	Finish	Voltage	Distribution	Lumen Package
VALA	M3R 3.8"	2FT 2 feet 3FT 3 feet 4FT 4 feet 8FT 8 feet *Connected	SCT Selectable 3000K 3500K 4000K	WT White BK *Black	UNV 120 - 277V	Blank 100% Down	LPS selectable High - 1200 lm/ft, 10w/ft Medium - 900 lm/ft, 7.5w/ft Low - 600 lm/ft, 5w/ft

*Connected: 120V continuous run up to 40FT. 277V continuous run up to 100FT. In increments of 4'. The fixture lengths come in 4' and 8'

*Black: black finish - consult factory for availability

MOUNTING OPTIONS & ACCESSORIES

Mounting Accessories	Joiner	Rolling Lens	EB Driver
SMA Surface and Wall Mount Kit (Square Plate + Male Quick Connector + Butterfly Drywall Anchor)	VA3.8CS - Line Joiner " - "	RL4 42" Continuous Rolling Diffusing Lens	EM-H08170 8w Emergency backup battery
FLS Recessed Flangeless Trim Drywall Ceiling (Trimless drywall recessed kit)	VA3.8CS - T Line Joiner " T "		EM-H25170 25w Emergency backup battery
FTD Recessed Flange Trim Drywall Ceiling (Trim drywall recessed kit)	VA3.8CS - + Line Joiner " + "		
GDC1A Recessed Grid Ceiling (Grid ceiling recessed kit for 2FT/3FT/4FT)	VA3.8CS - L Line Joiner " L "		
GDC1B Recessed Grid Ceiling (Grid ceiling recessed kit for 8FT only)			

Houston, Texas

Sales@orelighting.com

346-874-7955

www.orelighting.com

Note: Information contained herein is subject to change without notice.


©2024 ORE Lighting INC. All rights reserved

ORE LIGHTING

DIMENSIONS


VALA M3R - 2 Feet

2ft Length - Weight: 4.4 lbs.




VALA M3R - 3 Feet

3ft Length - Weight: 6.6 lbs.




VALA M3R - 4 Feet

4ft Length - Weight: 8.8 lbs.





VALA M3R - 8 Feet

8ft Length - Weight: 17.6 lbs.




VALA M3R



RECESSED CEILING MOUNT


TRIMLESS DRYWALL WOOD PANEL





Plaster Required




Flangeless Trim




TRIM DRYWALL




Flanged Trim




RECESSED IN GRID CEILING



T-Grid Hooks




VA3.8CS -
Straight Joiner



VA3.8CS - L
Line Joiner "L"



VA3.8CS - +
Line Joiner "+"



VA3.8CS - T
Line Joiner "T"






Rolling Lens
42ft Continuous


ORE LIGHTING

120V / 277V - CONTINUOUS RUN

120V Max run with single power feed up to 40ft
 270V Max run with single power feed up to 100ft



PHOTOMETRIC



VALA M3R 2FT&4FT

2FT			4FT		
ZONE	Lumens	%Lum	ZONE	Lumens	%Lum
FL(0-30)	301.0	13.9	FL(0-30)	588.1	18.4
FM(30-60)	421.8	25.9	FM(30-60)	818.0	25.6
FH(60-80)	66.8	4.1	FH(60-80)	134.5	4.2
FVH(80-90)	2.8	0.2	FVH(80-90)	5.5	0.2
BL(0-30)	306.2	18.8	BL(0-30)	601.5	18.9
BM(30-60)	447.7	27.5	BM(30-60)	880.1	27.6
BH(60-80)	72.1	4.4	BH(60-80)	148.1	4.6
BVH(80-90)	2.8	0.2	BVH(80-90)	5.4	0.2
UL(90-100)	0.1	0.0	UL(90-100)	0.3	0.0
UH(100-180)	4.5	0.3	UH(100-180)	8.7	0.3